# Forest Products Journal Index. . .1977

All the articles in the 1977 *Journal* are listed both by subject and by author. The Subject Index is organized according to the FPRS Division and Technical Committee structure.

The Author Index lists senior author entries which give complete information for the article, and co-author entries which refer back to the senior author.

Reprints of all the articles listed are available at a cost of 20¢ per printed page. Bulk rates are also available. The reprint number and cost per single reprint are listed for each entry. A check or money order must accompany each order.

# FPRS Subject Index . . . Vol. 27, 1977

## PRODUCTS DIVISION

### Bark & Residues

Continuous Tunnel Kiln Direct-Fired With Bark to Dry 1.75-Inch Southern Pine in 12 Hours, P. Koch and W. L. Wellford, Jr., 5:39 (No. 5646—$1.80).

Internal Bond and Moisture Response Properties of Three-Layer, Wood-Bark Boards, T. A. Place and T. M. Maloney, 3:50 (No. 5535—$1).

Investigation of Bark Residues for Livestock Bedding, J. N. McGovern, C. E. Zehner, and J. B. Boyle, 7:29 (No. 5572—$1.20).

Mesquite — a Possible Source of Energy, A. T. Wiley, 7:48 (No. 5624—$.80).

Method of Making Cellular Materials From Red Oak Bark, J. A. Galezewski, 12:21 (No. 5663—$.80).

Potential of the Utilization of Poultry Manure as a Source of Nitrogen in Composting Bark, J. Mater, 1:37 (No. 5531—$.80).

Production of Panelboard From Residue Left From the Fermentation of Organic Waste for Methane, C. S. Walters, J. T. Pfeffer, and P. Chow, 9:12 (No. 5666—$1.80).

Properties of Particleboard From Loblolly Pine Logging Residue, G. E. Coleman and E. J. Biblis, 9:49 (No. 5674—$1).

Some Mechanical Properties of Impregnated Bark Board, P. R. Blankenhorn, W. K. Murphey, L. E. Rishel, and D. E. Kline, 6:31 (No. 5614—$1.60).

Utilization of Bark Residues as Poultry Litter, P. Labosky, Jr., K. A. Holleman, J. W. Dick, and D. T. So, 1:28 (No. 5562—$1).

Variations in Effectiveness of Barks as Scavengers for Heavy Metal Ions, J. M. Randall, 11:51 (No. 5693—$1.20).

Wattle-Base Tannin-Starch Adhesives for Corrugated Containers, H. M. Saayman and C. H. Brown, 4:21 (No. 5566—$1).

### Construction Plywood

Computer Simulation of the Softwood Veneer-Drying Operation, H. Resch and H. L. Scheurman, 2:32 (No. 5560—$1).

Durability of Exterior Siding Plywood With Southeast Asian Hardwood Veneers, J. D. Wellons, R. L. Krahmer, R. Raymond, and G. Sleet, 2:38 (No. 5583—$1.40).

Effect of Moisture Content on Shear-Through-Thickness Strength of Douglas-fir Plywood, L. C. Palka, 2:54 (No. 5597—$.80).

Effect of Moisture Content on the Mechanical Properties of Douglas-fir Plywood in Rolling Shear, L. C. Palka and J. Hejjas, 4:49 (No. 5603—$1).

Fast Method for Estimating the Oven-dry Specific Gravity of Plywood, L. C. Palka, 8:35 (TN-322—$.40).

Heating Times for Frozen Veneer Logs—New Experimental Data, H. P. Steinhagen, 6:24 (No. 5596—$1).

### Decorative Veneers & Plywood

Durability of Exterior Siding Plywood With Southeast Asian Hardwood Veneers, J. D. Wellons, R. L. Krahmer, R. Raymond, and G. Sleet, 2:38 (No. 5583—$1.40).

### Hardboard & Insulation Board

Density Profile and Fiber Alignment in Fiberboard From Three Southern Hardwoods, G. E. Woodson, 8:29 (No. 5621—$1.20).

High-Frequency and Hot-Platen Curing of Medium-Density Fiberboards, R. R. Stevens and G. E. Woodson, 1:46 (No. 5550—$1).

Production of Panelboard From Residue Left From the Fermentation of Organic Waste for Methane, C. S. Walters, J. T. Pfeffer, and P. Chow, 9:12 (No. 5666—$1.80).

Properties of Veneered Southern Pine Low-Density Fiberboard From Hardwood Total-Tree Chips, M. W. Kelly and R. G. Pearson, 9:28 (No. 5685—$2).

Some Mechanical Properties of Impregnated Bark Board, P. R. Blankenhorn, W. K. Murphey, L. E. Rishel, and D. E. Kline, 6:31 (No. 5614—$1.60).

### Hardwood Lumber

Kiln-Drying Lumber From American Elm Trees Killed by Dutch Elm Disease, R. S. Boone and J. C. Ward, 5:48 (No. 5634—$.60).

Major Routes to Achieve Stress-Graded Hardwoods, W. L. Galligan, 2:21 (No. 5539—$1.20).

Reducing Crook in Kiln-Dried Northern Aspen Studs, J. F. G. Mackay, E. A. Hamm, and R. O. Foschi, 3:33 (No. 5574—$1.20).

Stress-Graded Hardwood Lumber by Press-Lam Production?, E. L. Schaffer and R. C. Moody, 2:26 (No. 5540—$1.20).

Value Yield From Simulated Hardwood Log Sawing, D. B. Richards, 12:47 (No. 5682—$.80).

Yield of Yellow-poplar Structural Dimension From Low-Grade Saw Logs, C. B. Koch and W. T. Rousis, 4:44 (No. 5594—$1).

### Laminated Wood, Components & Engineered Structures

Bending Strength of Small Glulam Beams With a Laminated-Veneer Tension Lamination, M. O. Braun and R. C. Moody, 11:46 (No. 5692—$1.20).

Computer-Assisted Experimental Design in Forest Products Research: a Case Study Based on Testing the Duration-of-Load Effect, W. G.

Warren and B. Madsen, 3:45 (No. 5579—$1.20).

Creep of Particleboard and Plywood Floor Deck Under Concentrated Loading, H. Hall, J. Haygreen, and B. Neisse, 5:23 (No. 5592—$2).

Limit States Design in Wood: a Canadian Perspective. State-of-the-Art Report. E. N. Aplin and F. J. Keenan, 7:14 (No. 5665—$1).

Minimum Slope on Flat Roof Systems — to Avoid Ponding, B. Chang and K. P. Chong, 7:35 (No. 5604—$.60).

Pilot Test of Four 16-Foot, Wood-Base Composite Garage Headers, D. H. Percival, M. O. Hunt, Q. B. Comus, and S. K. Suddarth, 9:45 (No. 5548—$.80).

Reliability-Based Design Procedures for Wood Structures, J. J. Zahn, 3:21 (No. 5591—$1.60).

Stochastic Model for Simulating the Distribution of Modulus of Elasticity in Samples of MSR Lumber, K. M. Brown, 4:39 (No. 5462—$1.20).

Strength and Stiffness of Walls With Wood and Steel Studs, A. Polensek, 2:45 (No. 5543—$1.80).

Stress-Graded Hardwood Lumber by Press-Lam Production?, E. L. Schaffer and R. C. Moody, 2:26 (No. 5540—$1.20).

Two-Way Action of Pitched Roofs, C. A. Nicol-Smith, 5:55 (TN-330—$.20).

Wood Column Design With Variable Parameters Using Computers and Plotters, L. W. Neubauer, J. R. Goss, and D. C. Hudson, 4:26 (No. 5536—$1).

## Pallets & Containers

Vacuum Loading Technique Increases Accuracy of Pallet Testing, J. E. Dallas and R. C. Mitzner, 6:48 (TN-333—$.60).

## Particleboard & Molded Products

Compression Shear Test for Determination of Internal Bond Strength in Particleboard, O. Suchsland, 1:32 (No. 5576—$1).

Effects of Furnish Type on Properties of Thin, Reconstituted Wood Panels, 3:38 (No. 5627—$1.40).

Effects of Several Test Variables on Evaluation of Particleboard Abrasiveness, R. R. Stevens and A. W. Fairbanks, Jr., 11:37 (No. 5653—$.80).

Internal Bond and Moisture Response Properties of Three-Layer, Wood-Bark Boards, T. A. Place and T. M. Maloney, 3:50 (No. 5535—$1).

Method of Making Cellular Materials From Red Oak Bark, J. A. Galezewski, 12:21 (No. 5663—$.80).

Properties of Particleboard From Loblolly Pine Logging Residue, G. E. Coleman and E. J. Biblis, 9:49 (No. 5674—$1).

Spent Sulfite Liquor Binder for Exterior Waferboard — a Progress Report, K. C. Shen, 5:32 (No. 5617—$1.40).

Structural Flakeboard Stiffness — Relation to Deflection Criteria and Economic Performance, H. D. Turner, 12:31 (No. 5508—$1).

## Pulp & Paper

Wattle-Base Tannin-Starch Adhesives for Corrugated Containers, H. M. Saayman and C. H. Brown, 4:21 (No. 5566—$1).

## Residential & Commercial Buildings

Limit States Design in Wood: a Canadian Perspective. State-of-the-Art Report. E. N. Aplin and F. J. Keenan, 7:14 (No. 5665—$1).

Pilot Test of Four 16-Foot, Wood-Base Composite Garage Headers, D. H. Percival, M. O. Hunt, Q. B. Comus, and S. K. Suddarth, 9:45 (No. 5548—$.80)

Strength and Stiffness of Walls With Wood and Steel Studs, A. Polensek, 2:45 (No. 5543—$1.80).

Two-Way Action of Pitched Roofs, C. A. Nicol-Smith, 5:55 (TN-330—$.20).

## Softwood Lumber

Continuous Tunnel Kiln Direct-Fired With Bark to Dry 1.75-Inch Southern Pine in 12 Hours, P. Koch and W. L. Wellford, Jr., 5:39 (No. 5646—$1.80).

Durability of Douglas-fir Heartwood From Coastal and Interior Sources, D. J. Miller and R. D. Graham, 12:29 (TN-346—$.40).

Export Markets for British Columbia Softwood Lumber Producers: Economic Theory vs. Empirical Evidence, G. H. Manning, 10:79 (No. 5781—$1).

High-Temperature Drying Effect on the Bending Strength of Spruce-Pine-Fir Joists, D. R. Huffman, 3:55 (No. 5598—$.60).

Moisture Content Control in Drying Dimension Lumber, G. Bramhall and W. G. Warren, 7:26 (No. 5701—$.60).

Selection of Strength Pieces by Nondestructive Testing: Douglas-fir and Hem-Fir 2 by 4s in Flexure, J. W. Johnson, 8:53 (TN-334—$.80).

Stochastic Model for Simulating the Distribution of Modulus of Elasticity in Samples of MSR Lumber, K. M. Brown, 4:39 (No. 5462—$1.20).

Treatability of Western Hemlock Lumber From Coastal and Interior British Columbia Regions With Waterborne Preservatives, P. A Cooper and N. A. Ross, 12:36 (No. 5524—$.80).

## Treated Wood Products

All Weather Wood Foundation — a Truly New Market for Wood, W. A. Dost, 11:17 (TN-347—$.40).

Comparison of a Quaternary Ammonium Compound and Copper-Chrome-Arsenate as Wood Preservatives, J. A. Butcher, M. E. Hedley, and J. Drysdale, 7:22 (No. 5616—$.80).

Durability of Douglas-fir Heartwood From Coastal and Interior Sources, D. J. Miller and R. D. Graham, 12:29 (TN-346—$.40).

Durability of Exterior Wood Stains, W. C. Feist, E. A. Mraz, and J. M. Black, 1:13 (No. 5565—$.80).

Final Results of 15-Year Post Study of Treatment With Powdered Reagents, E. A. Behr, 11:20 (No. 5697—$1.20).

Fungitoxicity of Pentachlorophenol Having Reduced Impurities, T. L. Amburgey, 11:18 (No. 5658—$.40).

Influence of Surface Treatments on the Properties of Weathered Particleboards, U. A. Meierhofer and J. Sell, 9:24 (No. 5575—$.80).

Initial Screening Trials of Some Quaternary Ammonium Compounds and Amine Salts as Wood Preservatives, J. A. Butcher, A. F. Preston, and J. Drysdale, 7:19 (No. 5615—$.80).

Loss of Creosote From Douglas-fir Marine Piles, D. J. Miller, 11:28 (No. 5684—$1.20).

Pentachlorophenol—Possible Sources of Human Exposure, R. S. Detrick, 6:13 (No. 5534—$.80).

Potential of the Utilization of Poultry Manure as a Source of Nitrogen in Composting Bark, J. Mater, 1:37 (No. 5531—$.80).

Treatability of Western Hemlock Lumber From Coastal and Interior British Columbia Regions With Waterborne Preservatives, P. A. Cooper and N. A. Ross, 12:36 (No. 5524—$.80).

Treatment of Softwoods with CCA at High Moisture Levels, P. F. Coetzee and A. van Laar, 7:38 (No. 5713—$1).

Treatment of Spruce Roundwood With a New CAA Preservative. Part I. Preservative Retention and Penetration, J. Rak, 8:36 (No. 5520—$1).

# PROCESSES DIVISION

## Drying & Storage

Computer Simulation of the Softwood Veneer-Drying Operation, H. Resch and H. L. Scheurman, 2:32 (No. 5560—$1).

Continuous Tunnel Kiln Direct-Fired With Bark to Dry 1.75-Inch Southern Pine in 12 Hours, P. Koch and W. L. Wellford, Jr., 5:39 (No. 5646—$1.80).

End Effect in Kiln-Drying, E. M. Wengert, 7:55 (TN-335—$.40).

Energy Conservation in Timber-Drying Kilns by Vapor Recompression, W. Miller, 9:54 (No. 5659—$1).

Evaluation of a New Portable Radiofrequency Moisture Meter on Lumber With Drying Gradients, J. R. Dennis and F. C. Beall, 8:24 (No. 5626—$1.20).

Formation of Checks in Tree Stems During Heating, H. Kubler, 1:41 (No. 5557—$1.20).

High-Temperature Drying Effect on the Bending Strength of Spruce-Pine-Fir Joists, D. R. Huffman, 3:55 (No. 5598—$.60).

Kiln-Drying Lumber From American Elm Trees Killed by Dutch Elm Disease, R. S. Boone and J. C. Ward, 5:48 (No. 5634—$.60).

Microwave Drying of Ponderosa Pine Cross-Sectional Disks, P. Illingworth and H. Klein Jr., 2:36 (TN-323—$.40).

Moisture Content Control in Drying Dimension Lumber, G. Bramhall and W. G. Warren, 7:26 (No. 5701—$.60).

Prototype Jet Impingement Dryer, H. N. Rosen, 11:34 (TN-337—$.80).

Reducing Crook in Kiln-Dried Northern Aspen Studs, J. F. G. Mackay, E. A. Hamm, and R. O. Foschi, 3:33 (No. 5574—$1.20).

### Energy Conservation

Energy Conservation in Timber-Drying Kilns by Vapor Recompression, W. Miller, 9:54 (No. 5659—$1).

Mesquite—a Possible Source of Energy, A. T. Wiley, 7:48 (No. 5624—$.80).

### Finishing & Overlaying

Durability of Exterior Wood Stains, W. C. Feist, E. A. Mraz, and J. M. Black, 1.13 (No. 5565—$.80).

Influence of Surface Treatments on the Properties of Weathered Particleboards, U. A. Meierhofer and J. Sell, 9:24 (No. 5575—$.80).

Wood Surface Treatments to Prevent Extractive Staining of Paints, W. C. Feist, 5:50 (No. 5656—$1).

### Gluing

Durability of Exterior Siding Plywood With Southeast Asian Hardwood Veneers, J. D. Wellons, R. L. Krahmer, R. Raymond, and G. Sleet, 2:38 (No. 5583—$1.40).

High-Frequency and Hot-Platen Curing of Medium-Density Fiberboards, R. R. Stevens and G. E. Woodson, 1:46 (No. 5550—$1).

Method for Measuring Resin Penetration Into Wood, M. S. White, G. Ifju, and J. A. Johnson, 7:52 (TN-332—$.60).

Method of Making Cellular Materials From Red Oak Bark, J. A. Galezewski, 12:21 (No. 5663—$.80).

Peroxyacetic Acid Bonding of Wood, W. E. Johns and T. Nguyen, 1:17 (No. 5553—$1.40).

Review of Filler and Extender Quality Evaluation, J. E. Robertson and R. R. P. Robertson, 4:30 (No. 5639—$1.80).

Some Mechanical Properties of Impregnated Bark Board, P. R. Blankenhorn, W. K. Murphey, L. E. Rishel, and D. E. Kline, 6:31 (No. 5614—$1.60).

Spent Sulfite Liquor Binder for Exterior Waferboard—a Progress Report, K. C. Shen, 5:32 (No. 5617—$1.40).

Thermal and Adhesive Characteristics of Acetone-Formaldehyde/Phenol-Formaldehyde Resins, P. R. Steiner, 9:38 (No. 5660—$1.20).

Wattle-Base Tannin-Starch Adhesives for Corrugated Containers, H. M. Saayman and C. H. Brown, 4:21 (No. 5566—$1).

### Mechanical Fastening

Comparison of Lag Screws and Threaded Nails in a Typical Structural Joint, R. B. Hoadley, 12:40 (No. 5273—$1.60).

Example of Integrated Research: Influence of Lumber Properties on Truss Performance, W. L. Galligan and E. Kallio, 11:12 (TN-358—$.80).

### Milling & Machining

Circular Saw Stiffness as a Measure of Tension, R. Szymani and C. D. Mote, Jr., 3:28 (No. 5577—$1).

Cutting Wood and Wood-Base Products With a Multikilowatt CO Laser, C. C. Peters and C. M. Banas, 11:41 (No. 5676—$1).

Effects of Several Test Variables on Evaluation of Particleboard Abrasiveness, R. R. Stevens and A. W. Fairbanks, Jr., 11:37 (No. 5653—$.80).

Forces in the Orthogonal Cutting of Rootwood and Stemwood From a Ponderosa Pine Tree, B. E. Klamecki, 11:26 (TN-342—$.40).

Optimum Rake Angle Related to Selected Strength Properties of Wood, H. A. Stewart, 1:51 (No. 5578—$.60).

### Pollution Abatement & Control

Internal Bond and Moisture Response Properties of Three-Layer, Wood-Bark Boards, T. A. Place and T. M. Maloney, 3:50 (No. 5535—$1).

Potential of the Utilization of Poultry Manure as a Source of Nitrogen in Composting Bark, J. Mater, 1:37 (No. 5531—$.80).

Production of Panelboard From Residue Left From the Fermentation of Organic Waste for Methane, C. S. Walters, J. T. Pfeffer, and P. Chow, 9:12 (No. 5666—$1.80).

### Timber Production

Beetle-Killed Lodgepole Pines Are Suitable for Powerpoles, A. C. Tegethoff, T. E. Hinds, and W. E. Eslyn, 9:21 (No. 5691—$.60).

Highlights From Wood for Structural and Architectural Purposes, C. W. Boyd, P. Koch, H. B. McKean, C. R. Morschauser, S. B. Preston, and F. F. Wangaard, 2:10 (No. 5675—$2.10).

Market Values and Problems Associated With Utilization of Dead Timber, T. A. Snellgrove and T. D. Fahey, 10:74 (No. 5780—$1.20).

Treatment of Spruce Roundwood With a New CAA Preservative. Part I. Preservative Retention and Penetration, J. Rak, 8:36 (No. 5520—$1).

Value Yield From Simulated Hardwood Log Sawing, D. B. Richards, 12:47 (No. 5682—$.80).

Yield of Yellow-poplar Structural Dimension From Low-Grade Saw Logs, C. B. Koch and W. T. Rousis, 4:44 (No. 5594—$1).

## MANAGEMENT

### Economics & Financial Management

Comparative Advantage and Potentials for World Trade in Wood Products, I. I. Holland, 10:55 (No. 5643—$.80).

Developments in Foreign Markets: the Case of Japan, R. L. Ethington, 10:59 (No. 5778—$.60).

Energy Conservation in Timber-Drying Kilns by Vapor Recompression, W. Miller, 9:54 (No. 5659—$1).

Export Horizons for the U.S. Solid Wood Industry, B. A. Austin, 10:67 (No. 5783—$1.40).

Export Markets for British Columbia Softwood Lumber Producers: Economic Theory vs. Empirical Evidence, G. H. Manning, 10:79 (No. 5781—$1).

Highlights From Wood for Structural and Architectural Purposes, C. W. Boyd, P. Koch, H. B. McKean, C. R. Morschauser, S. B. Preston, and F. F. Wangaard, 2:10 (No. 5675—$2.10).

How to Estimate Break-Even Points for Sawmill Improvement Projects, G. B. Harpole, 4:54 (No. 5618—$.60).

Market Values and Problems Associated With Utilization of Dead Timber, T. A. Snellgrove and T. D. Fahey, 10:74 (No. 5780—$1.20).

Mesquite— a Possible Source of Energy, A. T. Wiley, 7:48 (No. 5624—$.80).

Operations Research Applied to Noise Control in Sawmills, B. E. Klamecki, 8:41 (No. 5638—$1.20).

Outlook for Forest Products Trade and Imports, R. N. Stone and H. E. Dickerhoof, 10:44 (No. 5782—$1).

Structural Flakeboard Stiffness — Relation to Deflection Criteria and Economic Performance, H. D. Turner, 12:31 (No. 5508—$1).

U. S. Private Investment in Latin America, A. Contreras, 10:62 (No. 5707—$1).

Utilization Efficiency During Harvesting — a Survey of Current and Prospective Status, R. L. Porterfield, 12:17 (No. 5735—$.80).

Value Yield From Simulated Hardwood Log Sawing, D. B. Richards, 12:47 (No. 5682—$.80).

World Demand and Supply of Timber Products to the Year 2000, R. N. Stone and J. F. Saeman, 10:49 (No. 5732—$1.20).

### Marketing

Developments in Foreign Markets: the Case of Japan, R. L. Ethington, 10:59 (No. 5778—$.60).

Major Routes to Achieve Stress-Graded Hardwoods, W. L. Galligan, 2:21 (No. 5539—$1.20).

## Production Management

Continuous Tunnel Kiln Direct-Fired With Bark to Dry 1.75-Inch Southern Pine in 12 Hours, P. Koch and W. L. Wellford, Jr., 5:39 (No. 5646—$1.80).

Micro-Organisms Affecting Quality of Hardwood Trees Growing on Southern Pine Sites and of Products Made From Them — a Review, R. C. DeGroot and F. I. McCracken, 6:17 (No. 5600—$1.40).

Public Participation in Forest Industry Management Decisions, J. Mater and C. Mater, 8:16 (No. 5635—$.60).

## Quality Control

All Weather Wood Foundation — a Truly New Market for Wood, W. A. Dost, 11:17 (TN-347—$.40).

Compression Shear Test for Determination of Internal Bond Strength in Particleboard, O. Suchsland, 1:32 (No. 5576—$1).

Evaluation of a New Portable Radiofrequency Moisture Meter on Lumber With Drying Gradients, J. R. Dennis and F. C. Beall, 8:24 (No. 5626—$1.20).

Example of Integrated Research: Influence of Lumber Properties on Truss Performance, W. L. Galligan and E. Kallio, 11:12 (TN-358—$.80)

Moisture Content Control in Drying Dimension Lumber, G. Bramhall and W. G. Warren, 7:26 (No. 5701—$.60).

Review of Filler and Extender Quality Evaluation, J. E. Robertson and R. R. P. Robertson, 4:30 (No. 5639—$1.80).

Use of Performance Specifications in Wood Product Standards, M. N. Carroll, 8:46 (No. 5647—$1.40).

## Research Management

Automatic Processing of International Forest Products Statistics, J. Buongiorno, 4:16 (No. 5619—$1).

Computer-Assisted Experimental Design in Forest Products Research: a Case Study Based on Testing the Duration-of-Load Effect, W. G. Warren and B. Madsen, 3:45 (No. 5579—$1.20).

Limit States Design in Wood: a Canadian Perspective, State-of-the-Art Report, E. N. Aplin and F. J. Keenan, 7:14 (No. 5665—$1).

Lumber Truss Design—Views of Designers and Regulatory Agencies, W. L. Galligan, E. Kallio, and I. Sheppard, 12:25 (No. 5734—$1).

New Process for Guiding Public Research in Forest Products, J. G. Haygreen and R. L. Youngs, 12:14 (No. 5832—$.60).

Operations Research Applied to Noise Control in Sawmills, B. E. Klamecki, 8:41 (No. 5638—$1.20).

Public Participation in Forest Industry Management Decisions, J. Mater and C. Mater, 8:16 (No. 5635—$.60).

# FUNDAMENTAL DISCIPLINES DIVISION

## Biology

Comparison of a Quaternary Ammonium Compound and Copper-Chrome-Arsenate as Wood Preservatives, J. A. Butcher, M. E. Hedley, and J. Drysdale, 7:22 (No. 5616—$.80).

Durability of Exterior Wood Stains, W. C. Feist, E. A. Mraz, and J. M. Black, 1:13 (No. 5565—$.80).

Initial Screening Trials of Some Quaternary Ammonium Compounds and Amine Salts as Wood Preservatives, J. A. Butcher, A. F. Preston, and J. Drysdale, 7:19 (No. 5615—$.80).

Micro-Organisms Affecting Quality of Hardwood Trees Growing on Southern Pine Sites and of Products Made From Them — a Review, R. C. DeGroot and F. I. McCracken, 6:17 (No. 5600—$1.40).

Specific Gravity at Various Positions Along the Stem of Planted Loblolly Pine Trees, J. D. Lenhart, K. H. Shinn, and B. E. Cutter, 9:43 (No. 5650—$.40).

## Chemistry

Chemically Inducing Lightwood Formation in Southern Pines, D. R. Roberts and W. J. Peters, 6:28 (No. 5599—$.60).

Comparison of a Quaternary Ammonium Compound and Copper-Chrome-Arsenate as Wood Preservatives, J. A. Butcher, M. E. Hedley, and J. Drysdale, 7:22 (No. 5616—$.80).

Developments in Paraquat Treatment of Trees to Induce Lightwood Formation, J. Drew and D. R. Roberts, 7:43 (No. 5661—$1).

Durability of Exterior Siding Plywood With Southeast Asian Hardwood Veneers, J. D. Wellons, R. L. Krahmer, R. Raymond, and G. Sleet, 2:38 (No. 5583—$1.40).

Initial Screening Trials of Some Quaternary Ammonium Compounds and Amine Salts as Wood Preservatives, J. A. Butcher, A. F. Preston, and J. Drysdale, 7:19 (No. 5615—$.80).

Pentachlorophenol—Possible Sources of Human Exposure, R. S. Detrick, 6:13 (No. 5534—$.80).

Peroxyacetic Acid Bonding of Wood, W. E. Johns and T. Nguyen, 1:17 (No. 5553—$1.40).

Treatment of Softwoods With CCA at High Moisture Levels, P. F. Coetzee and A. van Laar, 7:38 (No. 5713—$1).

Variations in Effectiveness of Barks as Scavengers for Heavy Metal Ions, J. M. Randall, 11:51 (No. 5693—$1.20).

Wood Surface Treatments to Prevent Extractive Staining of Paints, W. C. Feist, 5:50 (No. 5656—$1).

## Physics

Density Profile and Fiber Alignment in Fiberboard From Three Southern Hardwoods, G. E. Woodson, 8:29 (No. 5621—$1.20).

Dielectric Behavior of Douglas-fir at Various Combinations of Temperature, Frequency, and Moisture Content, W. L. James, 6:44 (No. 5640—$1).

Evaluation of a New Portable Radiofrequency Moisture Meter on Lumber With Drying Gradients, J. R. Dennis and F. C. Beall, 8:24 (No. 5626—$1.20).

Fast Method for Estimating the Oven-dry Specific Gravity of Plywood, L. C. Palka, 8:35 (TN-322—$.40).

Formation of Checks in Tree Stems During Heating, H. Kubler, 1:41 (No. 5557—$1.20).

Heating Times for Frozen Veneer Logs — New Experimental Data, H. P. Steinhagen, 6:24 (No. 5596—$1).

High-Frequency and Hot-Platen Curing of Medium-Density Fiberboards, R. R. Stevens and G. E. Woodson, 1:46 (No. 5550—$1).

Method for Measuring Resin Penetration Into Wood, M. S. White, G. Ifju, and J. A. Johnson, 7:52 (TN-332—$.60).

Microwave Drying of Ponderosa Pine Cross-Sectional Disks, P. Illingworth and H. Klein, Jr., 2:36 (TN-323—$.40).

Operations Research Applied to Noise Control in Sawmills, B. E. Klamecki, 8:41 (No. 5638—$1.20).

Peroxyacetic Acid Bonding of Wood, W. E. Johns and T. Nguyen, 1:17 (No. 5553—$1.40).

Relationships Between Transverse Free Vibration E and Other Properties as Affected by Knots, I. Orosz, 1:23 (No. 5554—$1).

Specific Gravity at Various Positions Along the Stem of Planted Loblolly Pine Trees, J. D. Lenhart, K. H. Shinn, and B. E. Cutter, 9:43 (No. 5650—$.40).

Stress Wave Attenuation as an Indicator of Lumber Strength, J. H. Kaiserlik and R. F. Pellerin, 6:39 (No. 5623—$1).

## Wood Engineering & Mechanical Properties

Bending Strength of Small Glulam Beams With a Laminated-Veneer Tension Lamination, M. O. Braun and R. C. Moody, 11:46 (No. 5692—$1.20).

Comparison of Lag Screws and Threaded Nails in a Typical Structural Joint, R. B. Hoadley, 12:40 (No. 5273—$1.60).

Compression Shear Test for Determination of Internal Bond Strength in Particleboard, O. Suchsland, 1:32 (No. 5576—$1).

Computer-Assisted Experimental Design in Forest Products Research:

a Case Study Based on Testing the Duration-of-Load Effect, W. G. Warren and B. Madsen, 3:45 (No. 5579—$1.20).

Creep of Particleboard and Plywood Floor Deck Under Concentrated Loading, H. Hall, J. Haygreen, and B. Neisse, 5:23 (No. 5592—$2).

Density Profile and Fiber Alignment in Fiberboard From Three Southern Hardwoods, G. E. Woodson, 8:29 (No. 5621—$1.20).

Effects of Furnish Type on Properties of Thin, Reconstituted Wood Panels, 3:38 (No. 5627—$1.40).

Effect of Moisture Content on Shear-Through-Thickness Strength of Douglas-fir Plywood, L. C. Palka, 2:54 (No. 5597—$.80).

Effect of Moisture Content on the Mechanical Properties of Douglas-fir Plywood in Rolling Shear, L. C. Palka and J. Hejjas, 4:49 (No. 5603—$1).

Example of Integrated Research: Influence of Lumber Properties on Truss Performance, W. L. Galligan and E. Kallio, 11:12 (TN-358—$.80).

Forces in the Orthogonal Cutting of Rootwood and Stemwood From a Ponderosa Pine Tree, B. E. Klamecki, 11:26 (TN-342—$.40).

High-Frequency and Hot-Platen Curing of Medium-Density Fiberboards, R. R. Stevens and G. E. Woodson, 1:46 (No. 5550—$1).

High-Temperature Drying Effect on the Bending Strength of Spruce-Pine-Fir Joists, D. R. Huffman, 3:55 (No. 5598—$.60).

Limit States Design in Wood: a Canadian Perspective, State-of-the-Art Report, E. N. Aplin and F. J. Keenan, 7:14 (No. 5665—$1).

Longitudinal Shear Strength of Timber Beams, J. Longworth, 8:19 (No. 5606—$1).

Lumber Truss Design—Views of Designers and Regulatory Agencies, W. L. Galligan, E. Kallio, and I. Sheppard, 12:25 (No. 5734—$1).

Minimum Slope of Flat Roof Systems—to Avoid Ponding, B. Chang and K. P. Chong, 7:35 (No. 5604—$.60).

Optimum Rake Angle Related to Selected Strength Properties of Wood, H. A. Stewart, 1:51 (No. 5578—$.60).

Peroxyacetic Acid Bonding of Wood, W. E. Johns and T. Nguyen, 1:17 (No. 5553—$1.40).

Pilot Test of Four 16-Foot, Wood-Base Composite Garage Headers, D. H. Percival, M. O. Hunt, Q. B. Comus, and S. K. Suddarth, 9:45 (No. 5548—$.80).

Predicting Modulus of Rupture From Modulus of Elasticity for Small, Clear Specimens of Oak and Cottonwood, C. S. Walters and W. L. Reiss, 6:51 (No. 5649—$.60).

Properties of Veneered Southern Pine Low-Density Fiberboard From Hardwood Total-Tree Chips, M. W. Kelly and R. G. Pearson, 9:28 (No. 5685—$2).

Reducing Crook in Kiln-Dried Northern Aspen Studs, J. F. G. Mackay, E. A. Hamm, and R. O. Foschi, 3:33 (No. 5574—$1.20).

Relationships Between Transverse Free Vibration E and Other Properties as Affected by Knots, I. Orosz, 1:23 (No. 5554—$1).

Reliability-Based Design Procedures for Wood Structures, J. J. Zahn, 3:21 (No. 5591—$1.60).

Selection of Strength Pieces by Nondestructive Testing: Douglas-fir and Hem-Fir 2 by 4s in Flexure, J. W. Johnson, 8:53 (TN-334—$.80).

Some Mechanical Properties of Impregnated Bark Board, P. R. Blankenhorn, W. K. Murphey, L. E. Rishel, and D. E. Kline, 6:31 (No. 5614—$1.60).

Stochastic Model for Simulating the Distribution of Modulus of Elasticity in Samples of MSR Lumber, K. M. Brown, 4:39 (No. 5462—$1.20).

Strength and Stiffness of Walls With Wood and Steel Studs, A Polensek, 2:45 (No. 5543—$1.80).

Stress Wave Attenuation as an Indicator of Lumber Strength, J. H. Kaiserlik and R. F. Pellerin, 6:39 (No. 5623—$1).

Structural Flakeboard Stiffness — Relation to Deflection Criteria and Economic Performance, H. D. Turner, 12:31 (No. 5508—$1).

Two-Way Action of Pitched Roofs, C. A. Nicol-Smith, 5:55 (TN-330—$.20).

Wood Column Design With Variable Parameters Using Computers and Plotters, L. W. Neubauer, J. R. Goss, and D. C. Hudson, 4:26 (No. 5536—$1).

# FPRS Author Index . . . Vol. 27, 1977

## A


Amburgey, T. L., Fungitoxicity of Pentachlorophenol Having Reduced Impurities, 11:18 (No. 5658—$.40).

Aplin, E. N., and F. J. Keenan, Limit States Design in Wood: a Canadian Perspective. State-of-the-Art Report. 7:14 (No. 5665—$1).

Austin, B. A., Export Horizons for the U. S. Solid Wood Industry, 10:67 (No. 5783—$1.40).


## B


Banas, C. M., *see* Peters, C. C.

Beall, F. C., *see* Dennis, J. R.

Behr, E. A., Final Results of 15-Year Post Study of Treatment With Powdered Reagents, 11:20 (No. 5697—$1.20).

Biblis, E. J., *see* Coleman, G. E.

Black, J. M., *see* Feist, W. C.

Blankenhorn, P. R., W. K. Murphey, L. E. Rishel, and D. E. Kline, Some Mechanical Properties of Impregnated Bark Board, 6:31 (No. 5614—$1.60).

Boone, R. S., and J. C. Ward, Kiln-Drying Lumber From American Elm Trees Killed by Dutch Elm Disease, 5:48 (No. 5634— $.60).

Boyd, C. W., P. Koch, H. B. McKean, C. R. Morschauser, S. B. Preston, and F. F. Wangaard, Highlights From *Wood for Structural and Architectural Purposes*, 2:10 (No. 5675—$2.10).

Boyle, J. B., *see* McGovern, J. N.

Bramhall, G., and W. G. Warren, Moisture Content Control in Drying Dimension Lumber, 7:26 (No. 5701—$.60).

Braun, M. O., and R. C. Moody, Bending Strength of Small Glulam Beams With a Laminated-Veneer Tension Lamination, 11:46 (No. 5692—$1.20).

Brown, C. H., *see* Saayman, H. M.

Brown, K. M., Stochastic Model for Simulating the Distribution of Modulus of Elasticity in Samples of MSR Lumber, 4:39 No. 5462—$1.20).

Buongiorno, J., Automatic Processing of International Forest Products Statistics, 4:16 (No. 5619—$1).

Butcher, J. A., A. F. Preston, and J. Drysdale, Initial Screening Trials of Some Quaternary Ammonium Compounds and Amine Salts as Wood Preservatives, 7:19 (No. 5615—$.80).

Butcher, J. A., M. E. Hedley, and J. Drysdale, Comparison of a Quaternary Ammonium Compound and Copper-Chrome-Arsenate as Wood Preservatives, 7:22 (No. 5616—$.80)


## C


Carroll, M. N., Use of Performance Specifications in Wood Product Standards, 8:46 (No. 5647—$1.40).

Chang, B., and K. P. Chong, Minimum Slope on Flat Roof Systems—To Avoid Ponding, 7:35 (No. 5604—$.60).

Chong, K. P., *see* Chang, B.

Chow, P., *see* Walters, C. S.

Coetzee, P. F., and A. van Laar, Treatment of Softwoods With CCA at High Moisture Levels, 7:38 (No. 5713—$1).

Coleman, G. E., and E. J. Biblis, Properties of Particleboard From Loblolly Pine Logging Residue, 9:49 (No. 5674—$1).

Comus, Q. B., *see* Percival, D. H.

Contreras, A., U. S. Private Investment

in Latin America, 10:62 (No. 5707—$1).
Cooper, P. A., and N. A. Ross, Treatability of Western Hemlock Lumber From Coastal and Interior British Columbia Regions With Waterborne Preservatives, 12:36 (No. 5524—$.80).
Cutter, B. E., *see* Lenhart, J. D.

D

Dallas, J. E., and R. C. Mitzner, Vacuum Loading Technique Increases Accuracy of Pallet Testing, 6:48 (TN-333—$.60).
DeGroot, R. C., and F. I. McCracken, Micro-Organisms Affecting Quality of Hardwood Trees Growing on Southern Pine Sites and of Products Made From Them—a Review, 6:17 (No. 5600—$1.40).
Dennis, J. R., and F. C. Beall, Evaluation of a New Portable Radiofrequency Moisture Meter on Lumber With Drying Gradients, 8:24 (No. 5626—$1.20).
Detrick, R. S., Pentachlorophenol—Possible Sources of Human Exposure, 6:13 (No. 5534—$.80).
Dick, J. W., *see* Labosky, P., Jr.
Dickerhoof, H. E., *see* Stone, R. N.
Dost, W. A., All Weather Wood Foundation—a Truly New Market for Wood, 11:17 (TN-347—$.40).
Drew, J., and D. R. Roberts, Developments in Paraquat Treatment of Trees to Induce Lightwood Formation, 7:43 (No. 5661—$1).
Drysdale, J., *see* Butcher, J. A.
Drysdale, J., *see* Butcher, J. A.

E

Eslyn, W. E., *see* Tegethoff, A. C.
Ethington, R. L., Developments in Foreign Markets: the Case of Japan, 10:59 (No. 5778—$.60).

F

Fahey, T. D., *see* Snellgrove, T. A.
Fairbanks, A. W., Jr., *see* Stevens, R. R.
Feist, W. C., Wood Surface Treatments to Prevent Extractive Staining of Paints, 5:50 (No. 5656—$1).
Feist, W. C., E. A. Mraz, and J. M. Black, Durability of Exterior Wood Stains, 1:13 (No. 5565—$.80).
Foschi, R. O., *see* Mackay, J. F. G.

G

Galezewski, J. A. Method of Making Cellular Materials From Red Oak Bark, 12:21 (No. 5663—$.80).
Galligan, W. L., Major Routes to Achieve Stress-Graded Hardwoods, 2:21 (No. 5539—$1.20).
Galligan, W. L., and E. Kallio, Example of Integrated Research: Influence of Lumber Properties on Truss Performance, 11:12 (TN-358—$.80).
Galligan, W. L., E. Kallio, and I. Sheppard, Lumber Truss Design—Views of Designers and Regulatory Agencies, 12:25 (No. 5734—$1).
Goss, J. R., *see* Neubauer, L. W.
Graham, R. D., *see* Miller, D. J.

H

Hall, H., J. Haygreen, and B. Neisse, Creep of Particleboard and Plywood Floor Deck Under Concentrated Loading, 5:23 (No. 5592—$2.00).
Hamm, E. A., *see* Mackay, J. F. G.
Harpole, G. B., How to Estimate Break-Even Points for Sawmill Improvement Projects, 4:54 (No. 5618—$.60).
Haygreen, J. G., and R. L. Youngs, New Process for Guiding Public Research in Forest Products, 12:14 (No. 5832—$.60).
Haygreen, J. *see* Hall, H.
Hedley, M. E., *see* Butcher, J. A.
Hejjas, J., *see* Palka, L. C.
Hinds, T. E., *see* Tegethoff, A. C.
Hoadley, R. B., Comparison of Lag Screws and Threaded Nails in a Typical Structural Joint, 12:40 (No. 5273—$1.60).
Holland, I. I., Comparative Advantage and Potentials for World Trade in Wood Products, 10:55 (No. 5643—$.80).
Holleman, K. A. *see* Labosky, P., Jr.
Hudson, D. C., *see* Neubauer, L. W.
Huffman, D. R., High-Temperature Drying Effect on the Bending Strength of Spruce-Pine-Fir Joists, 3:55 (No. 5598—$.60).
Hunt, M. O. *see* Percival, D. H.

I

Ifju, G., *see* White, M. S.
Illingworth, P., and H. Klein, Jr., Microwave Drying of Ponderosa Pine Cross-Sectional Disks, 2:36 (TN-323—$.40).

J

James, W. L., Dielectric Behavior of Douglas-fir at Various Combinations of Temperature, Frequency, and Moisture Content, 6:44 (No. 5640—$1).
Johns, W. E., and T. Nguyen, Peroxyacetic Acid Bonding of Wood, 1:17 (No. 5553—$1.40).
Johnson, J. A., *see* White, M. S.
Johnson, J. W., Selection of Strength Pieces by Nondestructive Testing: Douglas-fir and Hem-Fir 2 by 4s in Flexure, 8:53 (TN-334—$.80).

K

Kaiserlik, J. H., and R. F. Pellerin, Stress Wave Attenuation as an Indicator of Lumber Strength, 6:39 (No. 5623—$1).
Kallio, E., *see* Galligan, W. L.
Kallio, E., *see* Galligan, W. L.
Keenan, F. J., *see* Aplin, E. N.
Kelly, M. W., and R. G. Pearson, Properties of Veneered Southern Pine Low-Density Fiberboard From Hardwood Total-Tree Chips, 9:28 (No. 5685—$2).
Klamecki, B. E., Forces in the Orthogonal Cutting of Rootwood and Stemwood From a Ponderosa Pine Tree, 11:26 (TN-342—$.40).
Klamecki, B. E., Operations Research Applied to Noise Control in Sawmills, 8:41 (No. 5638—$1.20).
Klein, H., Jr., *see* Illingworth, P.
Kline, D. E., *see* Blankenhorn, P. R.
Koch, C. B., and W. T. Rousis, Yield of Yellow-poplar Structural Dimension From Low-Grade Saw Logs, 4:44 (No. 5594—$1).
Koch, P., and W. L. Wellford, Jr., Continuous Tunnel Kiln Direct-Fired With Bark to Dry 1.75-Inch Southern Pine in 12 Hours, 5:39 (No. 5646—$1.80).
Koch, P., *see* Boyd, C. W.
Krahmer, R. L., *see* Wellons, J. D.
Kubler, H., Formation of Checks in Tree Stems During Heating, 1:41 (No. 5557—$1.20).

L

Labosky, P., Jr., K. A. Holleman, J. W. Dick, and D. T. So, Utilization of Bark Residues as Poultry Litter, 1:28 (No. 5562—$1).
Lenhart, J. D., K. H. Shinn, and B. E. Cutter, Specific Gravity at Various Positions Along the Stem of Planted Loblolly Pine Trees, 9:43 (No. 5650—$.40).
Longworth, J., Longitudinal Shear Strength of Timber Beams, 8:19 (No. 5606—$1).
Lyon, D. E., and P. H. Short, Effects of Furnish Type on Properties of Thin, Reconstituted Wood Panels, 3:38 (No. 5627—$1.40).

M

McCracken, F. I., *see* DeGroot, R. C.
McGovern, J. N., C. E. Zehner, and J. B. Boyle, Investigation of Bark Residues for Livestock Bedding, 7:29 (No. 5572—$1.20)
McKean, H. B., *see* Boyd, C. W.
Mackay, J. F. G., E. A. Hamm, and R. O. Foschi, Reducing Crook in Kiln-Dried Northern Aspen Studs, 3:33 (No. 5574—$1.20).
Madsen, B., *see* Warren, W. G.
Maloney, T. M., *see* Place, T. A.
Manning, G. H., Export Markets for British Columbia Softwood Lumber Producers: Economic Theory vs. Empirical Evidence, 10:79 (No. 5781—$1).
Mater, C., *see* Mater, J.
Mater, J., Potential of the Utilization of Poultry Manure as a Source of Nitrogen in Composting Bark, 1:37 (No. 5531—$.80).
Mater, J., and C. Mater, Public Participation in Forest Industry Management Decisions, 8:16 (No. 5635—$.60).
Meierhofer, U. A., and J. Sell, Influence of Surface Treatments on the Properties of Weathered Particleboards, 9:24 (No. 5575—$.80).
Miller, D. J., Loss of Creosote From Douglas-fir Marine Piles, 11:28 (No. 5684—$1.20)
Miller, D. J., and R. D. Graham, Durability of Douglas-fir Heartwood

From Coastal and Interior Sources, 12:29 (TN-346—$.40).
Miller, W., Energy Conservation in Timber-Drying Kilns by Vapor Recompression, 9:54 (No. 5659—$1).
Mitzner, R. C., *see* Dallas, J. E.
Moody, R. C., *see* Braun, M. O.
Moody, R. C., *see* Schaffer, E. L.
Morschauser, C. R., *see* Boyd, C. W.
Mote, C. D., Jr., *see* Szymani, R.
Mraz, E. A., *see* Feist, W. C.
Murphey, W. K., *see* Blankenhorn, P. R.

## N

Neisse, B., *see* Hall, H.
Neubauer, L. W., J. R. Goss, and D. C. Hudson, Wood Column Design With Variable Parameters Using Computers and Plotters, 4:26 (No. 5536—$1).
Nguyen, T., *see* Johns, W. E.
Nicol-Smith, C. A., Two-Way Action of Pitched Roofs, 5:55 (TN-330—$.20).

## O

Orosz, I., Relationships Between Transverse Free Vibration E and Other Properties as Affected by Knots, 1:23 (No. 5554—$1).

## P

Palka, L. C., Effect of Moisture Content on Shear-Through-Thickness Strength of Douglas-fir Plywood, 2:54 (No. 5597—$.80).
Palka, L. C., Fast Method for Estimating the Ovendry Specific Gravity of Plywood, 8:35 (TN-322—$.40).
Palka, L. C., and J. Hejjas, Effect of Moisture Content on the Mechanical Properties of Douglas-fir Plywood in Rolling Shear, 4:49 (No. 5603—$1).
Pearson, R. G., *see* Kelly, M. W.
Pellerin, R. F., *see* Kaiserlik, J. H.
Percival, D. H., M. O. Hunt, Q. B. Comus, and S. K. Suddarth, Pilot Test of Four 16-Foot, Wood-Base Composite Garage Headers, 9:45 (No. 5548—$.80).
Peters, C. C., and C. M. Banas, Cutting Wood and Wood-Base Products With a Multikilowatt $CO_2$ Laser, 11:41 (No. 5676—$1).
Peters, W. J., *see* Roberts, D. R.
Pfeffer, J. T., *see* Walters, C. S.
Place, T. A., and T. M. Maloney, Internal Bond and Moisture Response Properties of Three-Layer, Wood-Bark Boards, 3:50 (No. 5535—$1).
Polensek, A., Strength and Stiffness of Walls With Wood and Steel Studs, 2:45 (No. 5543—$1.80).
Porterfield, R. L., Utilization Efficiency During Harvesting—a Survey of Current and Prospective Status, 12:17 (No. 5735—$.80).
Preston, A. F., *see* Butcher, J. A.
Preston, S. B., *see* Boyd, C. W.

## R

Rak, J., Treatment of Spruce Roundwood With a New CAA Preservative. Part I. Preservative Retention and Penetration, 8:36 (No. 5520—$1).
Randall, J. M., Variations in Effectiveness of Barks as Scavengers for Heavy Metal Ions, 11:51 (No. 5693—$1.20).
Raymond, R., *see* Wellons, J. D.
Reiss, W. L., *see* Walters, C. S.
Resch, H., and H. L. Scheurman, Computer Simulation of the Softwood Veneer-Drying Operation, 2:32 (No. 5560—$1).
Richards, D. B., Value Yield From Simulated Hardwood Log Sawing, 12:47 (No. 5682—$.80).
Rishel, L. E., *see* Blankenhorn, P. R.
Roberts, D. R., and W. J. Peters, Chemically Inducing Lightwood Formation in Southern Pines, 6:28 (No. 5599—$.60).
Roberts, D. R., *see* Drew, J.
Robertson, J. E., and R. R. P. Robertson, Review of Filler and Extender Quality Evaluation, 4:30 (No. 5639—$1.80).
Robertson, R. R. P., *see* Robertson, J. E.
Rosen, H. N., Prototype Jet Impingement Dryer, 11:34 (TN-337—$.80).
Ross, N. A., *see* Cooper, P. A.
Rousis, W. T., *see* Koch, C. B.

## S

Saayman, H. M., and C. H. Brown, Wattle-Base Tannin-Starch Adhesives for Corrugated Containers, 4:21 (No. 5566—$1).
Saeman, J. F., *see* Stone, R. N.
Schaffer, E. L., and R. C. Moody, Stress-Graded Hardwood Lumber by Press-Lam Production?, 2:26 (No. 5540—$1.20).
Scheurman, H. L., *see* Resch, H.
Sell, J., *see* Meierhofer, U. A.
Shen, K. C., Spent Sulfite Liquor Binder for Exterior Waferboard—a Progress Report, 5:32 (No. 5617—$1.40).
Sheppard, I., *see* Galligan, W. L.
Shinn, K. H., *see* Lenhart, J. D.
Short, P. H., *see* Lyon, D. E.
Sleet, G., *see* Wellons, J. D.
Snellgrove, T. A., and T. D. Fahey, Market Values and Problems Associated With Utilization of Dead Timber, 10:74 (No. 5780—$1.20).
So, D. T., *see* Labosky, P., Jr.
Steiner, P. R., Thermal and Adhesive Characteristics of Acetone-Formaldehyde/Phenol-Formaldehyde Resins, 9:38 (No. 5660—$1.20).
Steinhagen, H. P., Heating Times for Frozen Veneer Logs—New Experimental Data, 6:24 (No. 5596—$1).
Stevens, R. R., and A. W. Fairbanks, Jr., Effects of Several Test Variables on Evaluation of Particleboard Abrasiveness, 11:37 (No. 5653—$.80).
Stevens, R. R., and G. E. Woodson, High-Frequency and Hot-Platen Curing of Medium-Density Fiberboards, 1:46 (No. 5550—$1).
Stewart, H. A., Optimum Rake Angle Related to Selected Strength Properties of Wood, 1:51 (No. 5578—$.60)
Stone, R. N., and H. E. Dickerhoof, Outlook for Forest Products Trade and Imports, 10:44 (No. 5782—$1).
Stone, R. N., and J. F. Saeman, World Demand and Supply of Timber Products to the Year 2000, 10:49 (No. 5732—$1.20).
Suchsland, O., Compression Shear Test for Determination of Internal Bond Strength in Particleboard, 1:32 (No. 5576—$1).
Suddarth, S. K., *see* Percival, D. H.
Szymani, R., and C. D. Mote, Jr., Circular Saw Stiffness as a Measure of Tension, 3:28 (No. 5577—$1).

## T

Tegethoff, A. C., R. E. Hinds, and W. E. Eslyn, Beetle-Killed Lodgepole Pines Are Suitable for Powerpoles, 9:21 (No. 5691—$.60).
Turner, H. D., Structural Flakeboard Stiffness—Relation to Deflection Criteria and Economic Performance, 12:31 (No. 5508—$1).

## V

Van Laar, A., *see* Coetzee, P. F.

## W

Walters, C. S., J. T. Pfeffer, and P. Chow, Production of Panelboard From Residue Left From the Fermentation of Organic Waste for Methane, 9:12 (No. 5666—$1.80).
Walters, C. S., and W. L. Reiss, Predicting Modulus of Rupture From Modulus of Elasticity for Small, Clear Specimens of Oak and Cottonwood, 6:51 (No. 5649—$.60).
Wangaard, F. F., *see* Boyd, C. W.
Ward, J. C., *see* Boone, R. S.
Warren, W. G., and B. Madsen, Computer-Assisted Experimental Design in Forest Products Research: a Case Study Based on Testing the Duration-of-Load Effect, 3:45 (No. 5579—$1.20).
Warren, W. G., *see* Bramhall, G.
Wellford, W. L., Jr., *see* Koch, P.
Wellons, J. D., R. L. Krahmer, R. Raymond, and G. Sleet, Durability of Exterior Siding Plywood With Southeast Asian Hardwood Veneers, 2:38 (No. 5583—$1.40).
Wengert, E. M., End Effect in Kiln-Drying, 7:55 (TN-335—$.40).
White, M. S., G. Ifju, and J. A. Johnson, Method for Measuring Resin Penetration Into Wood, 7:52 (TN-332—$.60).
Wiley, A. T., Mesquite—a Possible Source of Energy, 7:48 (No. 5624—$.80).
Woodson, G. E., Density Profile and Fiber Alignment in Fiberboard From Three Southern Hardwoods, 8:29 (No. 5621—$1.20).
Woodson, G. E., *see* Stevens, R. R.

## Y

Youngs, R. L., *see* Haygreen, J. G.

## Z

Zahn, J. J., Reliability-Based Design Procedures for Wood Structures, 3:21 (No. 5591—$1.60).
Zehner, C. E., *see* McGovern, J. N.